

Package: malariasimulation (via r-universe)

October 6, 2026

Title An individual based model for malaria

Version 3.0.0

Description Specifies the latest and greatest malaria model.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Remotes mrc-ide/malariaEquilibrium, mrc-ide/malariaEquilibriumVivax,
mrc-ide/individual

Imports individual ($\geq 0.1.17$), malariaEquilibrium ($\geq 1.0.1$),
malariaEquilibriumVivax, Rcpp, statmod, MASS, dqrng (≥ 0.4),
sitmo, BH, R6, progress

Suggests testthat, mockery, knitr, rmarkdown, reshape2, DiagrammeR,
cowplot, ggplot2, covr, mgcv

RoxygenNote 7.3.3

Roxygen list(markdown = TRUE)

LinkingTo Rcpp, individual, BH, testthat, dqrng, sitmo

VignetteBuilder knitr

Depends R (≥ 2.10)

Config/pak/sysreqs cmake make libuv1-dev

Repository <https://mrc-ide.r-universe.dev>

Date/Publication 2026-03-04 16:10:17 UTC

RemoteUrl <https://github.com/mrc-ide/malariasimulation>

RemoteRef master

RemoteSha 5f63ccd61c8e893892fd12e7580fc22a7c882285

Contents

AL_params	3
arab_params	3

calculate_carrying_capacity	4
CorrelationParameters	4
CQ_params_vivax	6
CQ_PQ_params_vivax	7
CQ_TQ_params_vivax	7
create_pev_profile	8
create_progress_process	8
DHA_PQP_params	9
find_birthrates	9
fun_params	10
gamb_params	10
get_antimalarial_resistance_parameters	11
get_correlation_parameters	11
get_init_carrying_capacity	12
get_parameters	13
kol_params	21
parameter_draws_pf	21
parameter_draws_pv	22
parameterise_mosquito_equilibrium	22
parameterise_total_M	23
parasite_parameters	23
peak_season_offset	24
r21_booster_profile	24
r21_profile	24
rtss_booster_profile	25
rtss_profile	25
run_metapop_simulation	26
run_resumable_simulation	27
run_simulation	27
run_simulation_with_repetitions	30
set_antimalarial_resistance	30
set_bednets	31
set_carrying_capacity	33
set_clinical_treatment	33
set_demography	34
set_drugs	34
set_epi_outputs	35
set_equilibrium	36
set_mass_pev	37
set_mda	38
set_parameter_draw	38
set_pev_epi	39
set_pmc	40
set_smc	40
set_species	41
set_spraying	41
set_tbv	42
SP_AQ_params	43

AL_params 3

steph_params 43

Index 44

AL_params	<i>Preset parameters for the AL drug (P. falciparum)</i>
-----------	--

Description

From SI of Commun. 5:5606 doi: 10.1038/ncomms6606 (2014)

Usage

AL_params

Format

An object of class numeric of length 4.

Details

Use a vector of preset parameters for the AL drug (artemether-lumefantrine)
Default parameters, from L to R, are: drug_efficacy: 0.95, drug_rel_c: 0.05094, drug_prophylaxis_shape: 11.3, drug_prophylaxis_scale: 10.6

arab_params	<i>Preset parameters for the An. arabiensis vector</i>
-------------	--

Description

Preset parameters for the An. arabiensis vector

Usage

arab_params

Format

An object of class list of length 7.

Details

Default parameters: species: "arab" blood_meal_rates: 0.3333333 foraging_time: .69 Q0: 0.71
phi_bednets: 0.8 phi_indoors: 0.86 mum: 0.132
parameters reference: Values for phi_bednets and phi_indoors are from: <https://www.pnas.org/content/pnas/early/2019/07/02>
Value for Q0 estimated in <https://journals.plos.org/plosmedicine/article?id=10.1371/journal.pmed.1000324>,
using data from these studies: <https://pubmed.ncbi.nlm.nih.gov/12943105/>, <https://link.springer.com/article/10.1186/1475-2875-7-136>, <https://pubmed.ncbi.nlm.nih.gov/14732241/> & <https://pubmed.ncbi.nlm.nih.gov/17199754/>

```
calculate_carrying_capacity
```

Calculate the vector carrying capacity

Description

taken from "Modelling the impact of vector control interventions on Anopheles gambiae population dynamics"

Usage

```
calculate_carrying_capacity(parameters, m, species)
```

Arguments

parameters	model parameters
m	number of adult mosquitoes
species	index of the species to calculate for

CorrelationParameters *Class: Correlation parameters*

Description

Class: Correlation parameters

Class: Correlation parameters

Details

This class implements functionality that allows interventions to be correlated, positively or negatively. By default, interventions are applied independently and an individual's probability of receiving two interventions (either two separate interventions or two rounds of the same one) is the product of the probability of receiving each one.

By setting a positive correlation between two interventions, we can make it so that the individuals that receive intervention A are more likely to receive intervention B. Conversely, a negative correlation will make it such that individuals that receive intervention A are less likely to also receive intervention B.

Broadly speaking, the implementation works by assigning at startup a weight to each individual and intervention pair, reflecting how likely an individual is to receive that intervention. Those weights are derived stochastically from the configured correlation parameters.

For a detailed breakdown of the calculations, see Protocol S2 of Griffin et al. (2010). Derive the mvnrm from the configured correlations.

If a restored_mvnrm is specified, its columns (corresponding to restored interventions) will be re-used as is. Missing columns (for new interventions) are derived in accordance with the restored data.

Methods

Public methods:

- `CorrelationParameters$new()`
- `CorrelationParameters$inter_round_rho()`
- `CorrelationParameters$inter_intervention_rho()`
- `CorrelationParameters$sigma()`
- `CorrelationParameters$mvnorm()`
- `CorrelationParameters$save_state()`
- `CorrelationParameters$restore_state()`
- `CorrelationParameters$clone()`

Method `new()`: initialise correlation parameters

Usage:

```
CorrelationParameters$new(population, interventions)
```

Arguments:

population population size

interventions character vector with the name of enabled interventions

Method `inter_round_rho()`: Add rho between rounds

Usage:

```
CorrelationParameters$inter_round_rho(int, rho)
```

Arguments:

int string representing the intervention to update

rho value between 0 and 1 representing the correlation between rounds of the intervention

Method `inter_intervention_rho()`: Add rho between interventions

Usage:

```
CorrelationParameters$inter_intervention_rho(int_1, int_2, rho)
```

Arguments:

int_1 string representing the first intervention

int_2 string representing the second intervention (intechangable with int_1)

rho value between -1 and 1 representing the correlation between rounds of the intervention

Method `sigma()`: Standard deviation of each intervention between rounds

Usage:

```
CorrelationParameters$sigma()
```

Method `mvnorm()`: multivariate norm draws for these parameters

Usage:

```
CorrelationParameters$mvnorm()
```

Method `save_state()`: Save the correlation state.

Usage:

CorrelationParameters\$save_state()

Method restore_state(): Restore the correlation state.

Only the randomly drawn weights are restored. The object needs to be initialized with the same rhos.

Usage:

CorrelationParameters\$restore_state(timestep, state)

Arguments:

timestep the timestep at which simulation is resumed. This parameter's value is ignored, it only exists to conform to a uniform interface.

state a previously saved correlation state, as returned by the save_state method.

Method clone(): The objects of this class are cloneable with this method.

Usage:

CorrelationParameters\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

CQ_params_vivax

Preset parameters for the CQ drug (P. vivax)

Description

Efficacy from SI of Nekkab et al., DOI: 10.1371/journal.pmed.1003535 (2021), shape and scale consistent with a longer prophylaxis time: 28 days, decreasing gradually

Usage

CQ_params_vivax

Format

An object of class numeric of length 7.

Details

Use a vector of preset parameters for the CQ drug (chloroquine) acting on P. vivax

Default parameters, from L to R, are: drug_efficacy: 0.899, drug_rel_c: 0.5, drug_prophylaxis_shape: 20, drug_prophylaxis_scale: 5

CQ_PQ_params_vivax	<i>Preset parameters for the CQ-PQ drug (P. vivax)</i>
--------------------	--

Description

Efficacy from SI of Nekkab et al., DOI: 10.1371/journal.pmed.1003535 (2021), BS shape and scale consistent with a longer prophylaxis time: 28 days, decreasing gradually, LS shape are scale consistent with a 7 day PQ treatment, with rapid decay.

Usage

CQ_PQ_params_vivax

Format

An object of class `numeric` of length 7.

Details

Use a vector of preset parameters for the CQ-PQ drug (chloroquine and primaquine) acting on *P. vivax*

Default parameters, from L to R, are: `drug_efficacy`: 0.948, `drug_rel_c`: 0.5, `drug_prophylaxis_shape`: 5, `drug_prophylaxis_scale`: 20, `drug_hypnozoite_efficacy`: 0.713, `drug_hypnozoite_prophylaxis_shape`: 10, `drug_hypnozoite_prophylaxis_scale`: 5.5

CQ_TQ_params_vivax	<i>Preset parameters for the CQ-TQ drug (P. vivax)</i>
--------------------	--

Description

Efficacy from SI of Nekkab et al., DOI: 10.1371/journal.pmed.1003535 (2021), BS shape and scale consistent with a longer prophylaxis time: 28 days, decreasing gradually, LS shape are scale consistent with a single TQ treatment, with longer prophylaxis: 45 days.

Usage

CQ_TQ_params_vivax

Format

An object of class `numeric` of length 7.

Details

Use a vector of preset parameters for the CQ-TQ drug (chloroquine and tafenoquine) acting on *P. vivax*

Default parameters, from L to R, are: drug_efficacy: 1, drug_rel_c: 0.5, drug_prophylaxis_shape: 5, drug_prophylaxis_scale: 20, drug_hypnozoite_efficacy: 0.713, drug_hypnozoite_prophylaxis_shape: 5.5, drug_hypnozoite_prophylaxis_scale: 30

create_pev_profile	<i>create a PEV profile</i>
--------------------	-----------------------------

Description

creates a data structure for holding pre-erythrocytic vaccine profile parameters. Parameters are validated on creation.

Usage

```
create_pev_profile(vmax, alpha, beta, cs, rho, ds, dl)
```

Arguments

vmax	maximum efficacy of the vaccine
alpha	shape parameter for the vaccine efficacy model
beta	scale parameter for the vaccine efficacy model
cs	peak parameters for the antibody model (vector of mean and std. dev)
rho	delay parameters for the antibody model (vector of mean and std. dev)
ds	delay parameters for the antibody model, short-term waning (vector of mean and std. dev)
dl	delay parameters for the antibody model, long-term waning (vector of mean and std. dev)

create_progress_process	<i>Create progress process</i>
-------------------------	--------------------------------

Description

Create progress process

Usage

```
create_progress_process(timesteps)
```

Arguments

timesteps	Simulation timesteps
-----------	----------------------

Value

Progress bar process function

DHA_PQP_params	<i>Preset parameters for the DHA-PQP drug (<i>P. falciparum</i>)</i>
----------------	--

Description

From SI of Commun. 5:5606 doi: 10.1038/ncomms6606 (2014)

Usage

DHA_PQP_params

Format

An object of class `numeric` of length 4.

Details

Use a vector of preset parameters for the DHA-PQP drug (dihydroartemisinin-piperaquine)

Default parameters, from L to R, are: `drug_efficacy`: 0.95, `drug_rel_c`: 0.09434, `drug_prophylaxis_shape`: 4.4, `drug_prophylaxis_scale`: 28.1

<code>find_birthrates</code>	<i>Calculate the birthrate for a population in equilibrium</i>
------------------------------	--

Description

Calculate the birthrate for a population in equilibrium

Usage

`find_birthrates(pops, age_high, deathrates)`

Arguments

<code>pops</code>	a vector of populations
<code>age_high</code>	a vector of age groups
<code>deathrates</code>	vector of deathrates for each age group

fun_params

Preset parameters for the An. funestus vector

Description

Preset parameters for the An. funestus vector

Usage

fun_params

Format

An object of class list of length 7.

Details

Default parameters: species: "fun" blood_meal_rates: 0.3333333 foraging_time: .69 Q0: 0.94
phi_bednets: 0.78 phi_indoors: 0.87 mum: 0.112

parameters reference: Values for phi_bednets and phi_indoors are from: <https://www.pnas.org/content/pnas/early/2019/07/02/10.1371/journal.pmed.1000324>,
Value for Q0 estimated by in <https://journals.plos.org/plosmedicine/article?id=10.1371/journal.pmed.1000324>,
using data from these studies: <https://pubmed.ncbi.nlm.nih.gov/18697309/>, <https://pubmed.ncbi.nlm.nih.gov/12943105/>
& <https://pubmed.ncbi.nlm.nih.gov/14732241/>

gamb_params

Preset parameters for the An. gambiae s.s vector

Description

Preset parameters for the An. gambiae s.s vector

Usage

gamb_params

Format

An object of class list of length 7.

Details

Default parameters: species: "gamb" blood_meal_rates: 0.3333333 foraging_time: .69 Q0: 0.92
phi_bednets: 0.85 phi_indoors: 0.90 mum: 0.132

parameters from: Values for phi_bednets and phi_indoors are from: <https://www.pnas.org/content/pnas/early/2019/07/02/10.1371/journal.pmed.1000324>,
Value for Q0 estimated in <https://journals.plos.org/plosmedicine/article?id=10.1371/journal.pmed.1000324>,
using data from these studies: <https://pubmed.ncbi.nlm.nih.gov/18697309/>, <https://pubmed.ncbi.nlm.nih.gov/12943105/>,
<https://link.springer.com/article/10.1186/1475-2875-7-136> & <https://pubmed.ncbi.nlm.nih.gov/14732241/>

```
get_antimalarial_resistance_parameters
```

Retrieve resistance parameters

Description

Retrieve the resistance parameters associated with the drug each individual receiving clinical treatment has been administered in the current time step.

Usage

```
get_antimalarial_resistance_parameters(parameters, drugs, timestep)
```

Arguments

parameters	the model parameters
drugs	vector of integers representing the drugs administered to each individual receiving treatment
timestep	the current time step

```
get_correlation_parameters
```

Get default correlation parameters

Description

returns a CorrelationParameters object for you edit. By default, all correlations are set to 0

Usage

```
get_correlation_parameters(parameters)
```

Arguments

parameters	model parameters
------------	------------------

Examples

```
# get the default model parameters
parameters <- get_parameters()

# Set some vaccination strategy
parameters <- set_mass_pev(
  parameters,
  profile = rtss_profile,
  timesteps = 100,
```

```

    coverages = .9,
    min_wait = 0,
    min_ages = 100,
    max_ages = 1000,
    booster_spacing = numeric(0),
    booster_coverage = numeric(0),
    booster_profile = NULL
  )

  # Set some smc strategy
  parameters <- set_drugs(parameters, list(SP_AQ_params))
  parameters <- set_smc(
    parameters,
    drug = 1,
    timesteps = 100,
    coverages = .9,
    min_age = 100,
    max_age = 1000
  )

  # Correlate the vaccination and smc targets
  correlations <- get_correlation_parameters(parameters)
  correlations$inter_intervention_rho('pev', 'smc', 1)

  # Correlate the rounds of smc
  correlations$inter_round_rho('smc', 1)

  # You can now pass the correlation parameters to the run_simulation function

```

```
get_init_carrying_capacity
```

Get initialised carrying capacity for each species

Description

Get initialised carrying capacity for each species

Usage

```
get_init_carrying_capacity(parameters)
```

Arguments

parameters the model parameters

Value

a vector of carrying initialised carrying capacity estimates for each vector species

get_parameters	<i>Get model parameters</i>
----------------	-----------------------------

Description

get_parameters creates a named list of parameters for use in the model. These parameters are passed to process functions.

The default parameters, which are for Plasmodium falciparum, are explained in "The US President's Malaria Initiative, Plasmodium falciparum transmission and mortality: A modelling study."

Plasmodium vivax specific parameters are explained in "Mathematical modelling of the impact of expanding levels of malaria control interventions on Plasmodium vivax." by White, Michael T., et al.

Usage

```
get_parameters(overrides = list(), parasite = "falciparum")
```

Arguments

overrides	a named list of parameter values to use instead of defaults
parasite	Plasmodium parasite species ("falciparum" or "vivax"); default = "falciparum" The parameters are defined below. parasite parameter <ul style="list-style-type: none"> • parasite - parasite species (falciparum or vivax); default = "falciparum" initial state proportions: <ul style="list-style-type: none"> • s_proportion - the proportion of human_population that begin as susceptible; default = 0.420433246 • d_proportion - the proportion of human_population that begin with clinical disease; default = 0.007215064 • a_proportion - the proportion of human_population that begin as asymptomatic; default = 0.439323667 • u_proportion - the proportion of human_population that begin as subpatents; default = 0.133028023 • t_proportion - the proportion of human_population that begin treated; default = 0 human fixed state transitions: <ul style="list-style-type: none"> • dd - the delay for humans to move from state D to A; default = 5 • dt - the delay for humans to move from state Tr to S; default = 5 • da - the delay for humans to move from state A to U; default = 195 • du - the delay for humans to move from state U to S (p.f only); default = 110 duration of pcr detectable infections: du (p.v only):

- dpcr_max - Maximum duration of PCR-detectable infections: default = 53.69
- dpcr_min - Minimum duration of PCR-detectable infections: default = 10
- kpcr - Shape parameter: default = 4.021
- apcr50 - Scale parameter: default = 9.8

human demography parameters:

- human_population - the initial number of humans to model; default = 100
- average_age - the average age of humans (in timesteps), this is only used if custom_demography is FALSE; default = 7665
- custom_demography - population demography given; default = FALSE

initial immunity values:

- init_ib - the initial pre-erythrocytic immunity (p.f only); default = 0
- init_iaa - the initial acquired anti-parasite immunity (p.v only); default = 0
- init_iam - the initial anti-parasite immunity at birth (p.v only); default = 0
- init_ica - the initial acquired immunity from clinical disease; default = 0
- init_icm - the initial clinical immunity at birth; default = 0
- init_iva - the initial acquired immunity from severe disease (p.f only); default = 0
- init_ivm - the initial severe immunity from severe disease at birth (p.f only); default = 0
- init_id - the initial acquired immunity to lm detectability (p.f only); default = 0

immunity decay rates:

- rb - decay rate for acquired pre-erythrocytic immunity (p.f only); default = 3650
- ra - decay rate for acquired anti-parasite immunity (p.v only); default = 3650
- rc - decay rate for acquired immunity to clinical disease; default = 10950
- rva - decay rate for acquired immunity to severe disease (p.f only); default = 10950
- rm - decay rate for maternal immunity to clinical disease (or p.v: maternal clinical and anti-parasite immunities); default = 67.6952
- rvm - decay rate for maternal immunity to severe disease (p.f only); default = 76.8365
- rid - decay rate for acquired immunity to lm-detectability (p.f only); default = 3650

immunity boost grace periods:

- ub - period in which pre-erythrocytic immunity cannot be boosted (p.f only); default = 7.2
- ua - period in which anti-parasite immunity cannot be boosted (p.v only); default = 44.09
- uc - period in which clinical immunity cannot be boosted; default = 6.06

- uv - period in which severe immunity cannot be boosted (p.f only); default = 11.4321
- ud - period in which immunity to detectability cannot be boosted (p.f only); default = 9.44512

maternal immunity parameters:

- pcm - new-born clinical immunity (or p.v: clinical and anti-parasite immunities) relative to mother's; default = 0.774368
- pvm - new-born severe immunity relative to mother's (p.f only); default = 0.195768

unique biting rate:

- a0 - age dependent biting parameter; default = 2920
- rho - age dependent biting parameter; default = 0.85
- sigma_squared - heterogeneity parameter; default = 1.67
- n_heterogeneity_groups - number discretised groups for heterogeneity, used for sampling mothers; default = 5

probability of pre-erythrocytic infection (p.f only):

- b0 - maximum probability due to no immunity; default = 0.59
- b1 - maximum reduction due to immunity; default = 0.5
- ib0 - scale parameter; default = 43.9
- kb - shape parameter; default = 2.16

probability of pre-erythrocytic infection (p.v only):

- b - probability of pre-erythrocytic infection: default = 0.25

probability of detection by light-microscopy when asymptomatic (p.f only):

- fd0 - time-scale at which immunity changes with age; default = 0.007055
- ad - scale parameter relating age to immunity; default = 7993.5
- gammad - shape parameter relating age to immunity; default = 4.8183
- d1 - minimum probability due to immunity; default = 0.160527
- id0 - scale parameter; default = 1.577533
- kd - shape parameter; default = 0.476614

probability of light-microscopy detectable infections due to anti-parasite immunity (p.v only):

- philm_max - maximum probability due to no immunity; default = 0.9329
- philm_min - maximum reduction due to immunity; default = 0.0131
- alm50 - scale parameter; default = 17.3
- klm - shape parameter; default = 3.202

probability of clinical infection:

- phi0 - maximum probability due to no immunity; default = 0.792
- phi1 - maximum reduction due to immunity; default = 0.00074
- ic0 - scale parameter; default = 18.02366
- kc - shape parameter; default = 2.36949

probability of severe infection (p.f only):

- theta0 - maximum probability due to no immunity; default = 0.0749886
- theta1 - maximum reduction due to immunity; default = 0.0001191
- iv0 - scale parameter; default = 1.09629
- kv - shape parameter; default = 2.00048
- fv0 - age dependent modifier; default = 0.141195
- av - age dependent modifier; default = 2493.41
- gammav - age dependent modifier; default = 2.91282

infectivity towards mosquitoes:

- cd - infectivity of clinically diseased humans towards mosquitoes; default = 0.068
- ca - infectivity of asymptomatic humans towards mosquitoes (p.v only); default = 0.1
- gamma1 - parameter for infectivity of asymptomatic humans; default = 1.82425
- cu - infectivity of subpatent infection; default = 0.0062
- ct - infectivity of treated infection; default = 0.021896

mosquito fixed state transitions (including mortality):

- del - the delay for mosquitoes to move from state E to L; default = 6.64
- dl - the delay for mosquitoes to move from state L to P; default = 3.72
- dpl - the delay mosquitoes to move from state P to Sm; default = 0.643
- me - early stage larval mortality rate; default = 0.0338
- ml - late stage larval mortality rate; default = 0.0348
- mup - the rate at which pupal mosquitoes die; default = 0.249
- mum - the rate at which developed mosquitoes die; default (An. gambiae) = .132

parameter variation parameters: please set parameter draw using the convenience function [set_parameter_draw](#)

- parameter_draw - the index of the parameter draw assigned using set_parameter_draw; default = NULL

vector biology: species specific values are vectors please set species parameters using the convenience function [set_species](#)

- beta - the average number of eggs laid per female mosquito per day; default = 21.2
- total_M - the initial number of adult mosquitos in the simulation; default = 1000
- init_foim - the FOIM used to calculate the equilibrium state for mosquitoes; default = 0
- species - names of the species in the simulation; default = "gamb"
- species_proportions - the relative proportions of each species; default = 1
- blood_meal_rates - the blood meal rates for each species; default = 1/3
- Q0 - proportion of blood meals taken on humans; default = 0.92
- foraging_time - time spent taking blood meals; default = 0.69

seasonality and carrying capacity parameters: please set flexible carrying capacity using the convenience function [set_carrying_capacity](#)

- model_seasonality - boolean switch TRUE iff the simulation models seasonal rainfall; default = FALSE
- g0 - rainfall fourier parameter; default = 2
- g - rainfall fourier parameter; default = 0.3, 0.6, 0.9
- h - rainfall fourier parameters; default = 0.1, 0.4, 0.7
- gamma - effect of density dependence on late instars relative to early instars; default = 13.25
- rainfall_floor - the minimum rainfall value (must be above 0); default 0.001
- carrying_capacity; default = FALSE
- carrying_capacity_timesteps; default = NULL
- carrying_capacity_values; default = NULL#'

parasite incubation periods:

- de - duration of the human latent period of infection; default = 12
- delay_gam - lag from parasites to infectious gametocytes; default = 12.5
- dem - extrinsic incubation period in mosquito population model; default = 10

hypnozoite batch parameters (p.v only):

- f - hypnozoite batch relapse rate; default = 0.02439024
- gammal - hypnozoite batch clearance rate; default = 0.002610966
- init_hyp - initial hypnozoite batch number; default = 0
- kmax - maximum number of hypnozoite batches for use in the equilibrium solution; default = 10

treatment parameters: please set treatment parameters with the convenience functions [set_drugs](#) and [set_clinical_treatment](#)

- drug_efficacy - a vector of efficacies for available drugs; default = turned off
- drug_rel_c - a vector of relative onward infectiousness values for drugs; default = turned off
- drug_prophylaxis_shape - a vector of shape parameters for weibull curves to model prophylaxis for each drug; default = turned off
- drug_prophylaxis_scale - a vector of scale parameters for weibull curves to model prophylaxis for each drug; default = turned off
- drug_hypnozoite_efficacy - a vector of efficacies targeting hypnozoites; default = turned off
- drug_hypnozoite_prophylaxis_shape - a vector of shape parameters for weibull curves to model prophylaxis against hypnozoite batch formation (days); default = turned off
- drug_hypnozoite_prophylaxis_scale - a vector of scale parameters for weibull curves to model prophylaxis against hypnozoite batch formation (days); default = turned off

- `clinical_treatment_drugs` - a vector of drugs that are available for clinically diseased (these values refer to the index in `drug_*` parameters); default = NULL, NULL, NULL
- `clinical_treatment_coverage` - a vector of coverage values for each drug; default = NULL, NULL, NULL

MDA, SMC and PMC parameters: please set these parameters with the convenience functions `set_mda`, `set_smc` and `set_pmc`, with `peak_season_offset` bednet, irs and mosquito feeding cycle parameters: please set vector control strategies using `set_bednets` and `set_spraying`

- `bednets` - boolean for if bednets are enabled; default = FALSE
- `phi_bednets` - proportion of bites taken in bed; default = 0.85
- `k0` - proportion of females bloodfed with no net; default = 0.699
- `spraying` - boolean for if indoor spraying is enabled; default = FALSE
- `phi_indoors` - proportion of bites taken indoors; default = 0.90

PEV parameters: please set vaccine strategies with the convenience functions `set_pev_epi` and `set_mass_pev`

- `pev_doses` - the dosing schedule before the vaccine takes effect; default = `c(0, 1.5 * 30, 3 * 30)` default = 365

TBV parameters: please set TBV parameters with the convenience functions in `set_tbv`

- `tbv_mt` - effect on treated infectiousness; default = 35
- `tbv_md` - effect on diseased infectiousness; default = 46.7
- `tbv_ma` - effect on asymptomatic infectiousness; default = 3.6
- `tbv_mu` - effect on subpatent infectiousness; default = 0.8
- `tbv_k` - scale parameter for effect on infectiousness; default = 0.9
- `tbv_tau` - peak antibody parameter; default = 22
- `tbv_rho` - antibody component parameter; default = 0.7
- `tbv_ds` - antibody short-term delay parameter; default = 45
- `tbv_dl` - antibody long-term delay parameter; default = 591
- `tbv_tra_mu` - transmission reduction parameter; default = 12.63
- `tbv_gamma1` - transmission reduction parameter; default = 2.5
- `tbv_gamma2` - transmission reduction parameter; default = 0.06

Antimalarial resistance parameters: please set antimalarial resistance parameters with the convenience functions in `set_antimalarial_resistance`

- `antimalarial_resistance` - boolean for if antimalarial resistance is enabled; default = FALSE
- `antimalarial_resistance_drug` - vector of drugs for which resistance can be parameterised; default = NULL
- `antimalarial_resistance_timesteps` - vector of time steps on which resistance updates occur; default = NULL
- `artemisinin_resistant_proportion` - vector of proportions of infections resistant to the artemisinin component of a given drug; default = NULL

- partner_drug_resistance_proportion - vector of proportions of infections resistant to the partner drug component of a given drug; default = NULL
- slow_parasite_clearance_probability - vector of probabilities of slow parasite clearance for a given drug; default = NULL
- early_treatment_failure_probability - vector of probabilities of early treatment failure for a given drug; default = NULL
- late_clinical_failure_probability - vector of probabilities of late clinical failure for a given drug; default = NULL
- late_parasitological_failure_probability - vector of probabilities of late parasitological failure for a given drug; default = NULL
- reinfection_during_prophylaxis_probability - vector of probabilities of reinfection during prophylaxis for a given drug; default = NULL
- dt_slow_parasite_clearance - the delay for humans experiencing slow parasite clearance to move from state Tr to S; default = NULL

rendering: All values are in timesteps and all ranges are inclusive. Please set rendered age groups using the convenience function

- age_group_rendering_min_ages - the minimum ages for population size outputs; default = turned off
- age_group_rendering_max_ages - the corresponding max ages; default = turned off
- incidence_rendering_min_ages - the minimum ages for incidence outputs (includes asymptomatic microscopy +); default = turned off
- incidence_rendering_max_ages - the corresponding max ages; default = turned off
- clinical_incidence_rendering_min_ages - the minimum ages for clinical incidence outputs (symptomatic); default = 0
- clinical_incidence_rendering_max_ages - the corresponding max ages; default = 1825
- severe_incidence_rendering_min_ages - the minimum ages for severe incidence outputs; default = turned off
- severe_incidence_rendering_max_ages - the corresponding max ages; default = turned off
- prevalence_rendering_min_ages - the minimum ages for clinical prevalence outputs; default = 730
- prevalence_rendering_max_ages - the corresponding max ages; default = 3650
- n_with_hypnozoites_rendering_min_ages - the minimum ages for number with hypnozoites outputs (p.v only); default = numeric(0)
- n_with_hypnozoites_rendering_max_ages - the corresponding max ages; default = numeric(0)

Age structured mean immunity (/hyponozoite) rendering:

- ib_rendering_min_ages - the minimum ages for blood immunity outputs (p.f only); default = numeric(0)
- ib_rendering_max_ages - the corresponding max ages; default = numeric(0)

- `id_rendering_min_ages` - the minimum ages for acquired detectability immunity (p.f); default = `numeric(0)`
- `id_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `iaa_rendering_min_ages` - the minimum ages for antiparasite immunity (p.v only); default = `numeric(0)`
- `iam_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `ica_rendering_min_ages` - the minimum ages for acquired clinical immunity outputs; default = `numeric(0)`
- `ica_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `iva_rendering_min_ages` - the minimum ages for acquired severe immunity outputs (p.f only); default = `numeric(0)`
- `iva_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `idm_rendering_min_ages` - the minimum ages for maternal antiparasite immunity outputs (p.v only); default = `numeric(0)`
- `idm_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `icm_rendering_min_ages` - the minimum ages for maternal clinical immunity outputs; default = `numeric(0)`
- `icm_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `ivm_rendering_min_ages` - the minimum ages for maternal severe immunity outputs (p.f only); default = `numeric(0)`
- `ivm_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`
- `hypnozoites_rendering_min_ages` - the minimum ages average hypnozoite batches outputs (p.v only); default = `numeric(0)`
- `hypnozoites_rendering_max_ages` - the corresponding max ages; default = `numeric(0)`

mixing:

- `rdt_intercept` - the y intercept for the log logit relationship between rdt and PCR prevalence; default = -0.968
- `rdt_coeff` - the coefficient for the log logit relationship between rdt and PCR prevalence; default = 1.186

miscellaneous:

- `mosquito_limit` - the maximum number of mosquitoes to allow for in the simulation; default = 1.00E+05
- `individual_mosquitoes` - boolean whether adult mosquitoes are modeled individually or compartmentally; default = TRUE
- `human_population_timesteps` - the timesteps at which the population should change; default = 0
- `r_tol` - the relative tolerance for the ode solver; default = 1e-4
- `a_tol` - the absolute tolerance for the ode solver; default = 1e-4
- `ode_max_steps` - the max number of steps for the solver; default = 1e6
- `enable_heterogeneity` - boolean whether to include heterogeneity in biting rates; default = TRUE

`kol_params`*Preset parameters for the An. koliensis vector*

Description

Preset parameters for the An. koliensis vector

Usage

```
kol_params
```

Format

An object of class `list` of length 7.

Details

Default parameters: species: "kol" blood_meal_rates: 0.3333333 foraging_time: .68 Q0: 0.5
phi_bednets: 0.9 phi_indoors: 0.5 mum: 0.1666667

parameters reference: https://github.com/MWhite-InstitutPasteur/Pvivax_IBM/blob/master/koliensis_parameters.txt

Value for blood meal rate is assumed in absence of phi are from:

`parameter_draws_pf`*Parameter draws (P. falciparum)*

Description

A list of 1000 draws from the joint posterior fit from

Usage

```
parameter_draws_pf
```

Format

`parameter_draws_pf`:

A list of lists of length 1000, each level contains a list of drawn parameters

Source

<https://www.nature.com/articles/ncomms4136>

parameter_draws_pv	<i>Parameter draws (P. vivax)</i>
--------------------	-----------------------------------

Description

1000 draws from the joint posterior fit from

Usage

```
parameter_draws_pv
```

Format

```
parameter_draws_pv:
```

A list of lists of length 1000, each level contains a list of drawn parameters

Source

<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6097992/>

parameterise_mosquito_equilibrium	<i>Parameterise total_M and carrying capacity for mosquitos from EIR</i>
-----------------------------------	--

Description

NOTE: the inital EIR is likely to change unless the rest of the model is in equilibrium. NOTE: please set seasonality first, since the mosquito_limit will estimate an upper bound from the peak season.

max_total_M is calculated using the equilibrium solution from "Modelling the impact of vector control interventions on Anopheles gambiae population dynamics"

Usage

```
parameterise_mosquito_equilibrium(parameters, EIR)
```

Arguments

parameters	the parameters to modify
EIR	to work from

parameterise_total_M *Parameterise total_M*

Description

Sets total_M and an upper bound for the number of mosquitoes in the simulation. NOTE: please set seasonality first, since the mosquito_limit will estimate an upper bound from the peak season.

Usage

```
parameterise_total_M(parameters, total_M)
```

Arguments

parameters	the parameters to modify
total_M	the initial adult mosquitoes in the simulation

parasite_parameters *Parasite parameters*

Description

Parasite-specific parameters for P. falciparum and vivax for use in malariasimulation

Usage

```
parasite_parameters
```

Format

```
parasite_parameters:
A
```

Source

<https://www.nature.com/articles/ncomms4136>, <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6097992/>

peak_season_offset	<i>Calculate the yearly offset (in timesteps) for the peak mosquito season</i>
--------------------	--

Description

Calculate the yearly offset (in timesteps) for the peak mosquito season

Usage

```
peak_season_offset(parameters)
```

Arguments

parameters to work from

r21_booster_profile	<i>R21 booster vaccine profile</i>
---------------------	------------------------------------

Description

Parameters for a booster dose of R21 for use with the set_mass_pev and set_pev_epi functions (Schmit + Topazian et al. 2022 Lancet ID)

Usage

```
r21_booster_profile
```

Format

An object of class list of length 7.

r21_profile	<i>R21 vaccine profile</i>
-------------	----------------------------

Description

Parameters for a primary dose of R21 for use with the set_mass_pev and set_pev_epi functions (Schmit + Topazian et al. 2022 Lancet ID)

Usage

```
r21_profile
```

Format

An object of class list of length 7.

rtss_booster_profile	<i>RTS,S booster vaccine profile</i>
----------------------	--------------------------------------

Description

Parameters for a booster dose of RTS,S for use with the set_mass_pev and set_pev_epi functions (White MT et al. 2015 Lancet ID)

Usage

```
rtss_booster_profile
```

Format

An object of class list of length 7.

rtss_profile	<i>RTS,S vaccine profile</i>
--------------	------------------------------

Description

Parameters for a primary dose of RTS,S for use with the set_mass_pev and set_pev_epi functions (White MT et al. 2015 Lancet ID)

Usage

```
rtss_profile
```

Format

An object of class list of length 7.

run_metapop_simulation

Run a metapopulation model

Description

Run a metapopulation model

Usage

```
run_metapop_simulation(
    timesteps,
    parameters,
    correlations = NULL,
    mixing_tt,
    export_mixing,
    import_mixing,
    p_captured_tt,
    p_captured,
    p_success
)
```

Arguments

timesteps	the number of timesteps to run the simulation for (in days)
parameters	a list of model parameter lists for each population
correlations	a list of correlation parameters for each population (default: NULL)
mixing_tt	a vector of time steps for each mixing matrix
export_mixing	a list of matrices of coefficients for exportation of infectivity. Rows = origin sites, columns = destinations. Each matrix element describes the mixing pattern from destination to origin. Each matrix element must be between 0 and 1. Each matrix is activated at the corresponding timestep in mixing_tt
import_mixing	a list of matrices of coefficients for importation of infectivity.
p_captured_tt	a vector of time steps for each p_captured matrix
p_captured	a list of matrices representing the probability that travel between sites is intervened by a test and treat border check. Dimensions are the same as for export_mixing
p_success	the probability that an individual who has tested positive (through an RDT) successfully clears their infection through treatment

Value

a list of dataframe of model outputs as in run_simulation

run_resumable_simulation

Run the simulation in a resumable way

Description

this function accepts an initial simulation state as an argument, and returns the final state after running all of its timesteps. This allows one run to be resumed, possibly having changed some of the parameters.

Usage

```
run_resumable_simulation(
    timesteps,
    parameters = NULL,
    correlations = NULL,
    initial_state = NULL,
    restore_random_state = FALSE
)
```

Arguments

timesteps	the timestep at which to stop the simulation
parameters	a named list of parameters to use
correlations	correlation parameters
initial_state	the state from which the simulation is resumed
restore_random_state	if TRUE, restore the random number generator's state from the checkpoint.

Value

a list with two entries, one for the dataframe of results and one for the final simulation state.

run_simulation

Run the simulation

Description

Run the simulation for some time given some parameters. This currently returns a dataframe with the number of individuals in each state at each timestep.

The resulting dataframe contains the following columns:

- timestep: the timestep for the row
- infectivity: the infectivity from humans towards mosquitoes

- FOIM: the force of infection towards mosquitoes (per species)
- mu: the death rate of adult mosquitoes (per species)
- EIR: the Entomological Inoculation Rate (per timestep, per species, over the whole population)
- n_bitten: number of humans bitten by an infectious mosquito
- n_treated: number of humans treated for clinical or severe malaria this timestep
- n_infections: number of humans who get an asymptomatic, clinical or severe malaria this timestep
- natural_deaths: number of humans who die from aging
- S_count: number of humans who are Susceptible
- A_count: number of humans who are Asymptomatic
- D_count: number of humans who have the clinical malaria
- U_count: number of subpatent infections in humans
- Tr_count: number of detectable infections being treated in humans
- ica_mean: the mean acquired immunity to clinical infection over the population of humans
- icm_mean: the mean maternal immunity to clinical infection over the population of humans
- iva_mean: the mean acquired immunity to severe infection over the population of humans
- ivm_mean: the mean maternal immunity to severe infection over the population of humans
- ib_mean: the mean blood immunity to all infection over the population of humans
- id_mean: the mean immunity from detection through microscopy over the population of humans
- n: number of humans between an inclusive age range at this timestep. This defaults to n_730_3650. Other age ranges can be set with prevalence_rendering_min_ages and prevalence_rendering_max_ages parameters.
- n_detect_lm (or pcr): number of humans with an infection detectable by microscopy (or pcr) between an inclusive age range at this timestep. This defaults to n_detect_730_3650. Other age ranges can be set with prevalence_rendering_min_ages and prevalence_rendering_max_ages parameters.
- p_detect_lm (or pcr): the sum of probabilities of detection by microscopy (or pcr) between an inclusive age range at this timestep. This defaults to p_detect_730_3650. Other age ranges can be set with prevalence_rendering_min_ages and prevalence_rendering_max_ages parameters.
- n_inc: number of new infections for humans between an inclusive age range at this timestep. incidence columns can be set with incidence_rendering_min_ages and incidence_rendering_max_ages parameters.
- p_inc: sum of probabilities of infection for humans between an inclusive age range at this timestep. incidence columns can be set with incidence_rendering_min_ages and incidence_rendering_max_ages parameters.
- n_inc_clinical: number of new clinical infections for humans between an inclusive age range at this timestep. clinical incidence columns can be set with clinical_incidence_rendering_min_ages and clinical_incidence_rendering_max_ages parameters.

- `p_inc_clinical`: sub of probabilities of clinical infection for humans between an inclusive age range at this timestep. clinical incidence columns can be set with `clinical_incidence_rendering_min_ages` and `clinical_incidence_rendering_max_ages` parameters.
- `n_inc_severe`: number of new severe infections for humans between an inclusive age range at this timestep. severe incidence columns can be set with `severe_incidence_rendering_min_ages` and `severe_incidence_rendering_max_ages` parameters.
- `p_inc_severe`: the sum of probabilities of severe infection for humans between an inclusive age range at this timestep. severe incidence columns can be set with `severe_incidence_rendering_min_ages` and `severe_incidence_rendering_max_ages` parameters.
- `E_count`: number of mosquitoes in the early larval stage (per species)
- `L_count`: number of mosquitoes in the late larval stage (per species)
- `P_count`: number of mosquitoes in the pupal stage (per species)
- `Sm_count`: number of adult female mosquitoes who are Susceptible (per species)
- `Pm_count`: number of adult female mosquitoes who are incubating (per species)
- `Im_count`: number of adult female mosquitoes who are infectious (per species)
- `rate_D_A`: rate that humans transition from clinical disease to asymptomatic
- `rate_A_U`: rate that humans transition from asymptomatic to subpatent
- `rate_U_S`: rate that humans transition from subpatent to susceptible
- `net_usage`: the number people protected by a bed net
- `mosquito_deaths`: number of adult female mosquitoes who die this timestep
- `n_drug_efficacy_failures`: number of clinically treated individuals whose treatment failed due to drug efficacy
- `n_early_treatment_failure`: number of clinically treated individuals who experienced early treatment failure
- `n_successfully_treated`: number of clinically treated individuals who are treated successfully (includes individuals who experience slow parasite clearance)
- `n_slow_parasite_clearance`: number of clinically treated individuals who experienced slow parasite clearance

Usage

```
run_simulation(timesteps, parameters = NULL, correlations = NULL)
```

Arguments

<code>timesteps</code>	the number of timesteps to run the simulation for (in days)
<code>parameters</code>	a named list of parameters to use
<code>correlations</code>	correlation parameters

Value

dataframe of results

```
run_simulation_with_repetitions
```

Run the simulation with repetitions

Description

Run the simulation with repetitions

Usage

```
run_simulation_with_repetitions(
    timesteps,
    repetitions,
    parameters = NULL,
    correlations = NULL,
    parallel = FALSE
)
```

Arguments

timesteps	the number of timesteps to run the simulation for
repetitions	n times to run the simulation
parameters	a named list of parameters to use
correlations	correlation parameters
parallel	execute runs in parallel

```
set_antimalarial_resistance
```

Parameterise antimalarial resistance

Description

Parameterise antimalarial resistance

Usage

```
set_antimalarial_resistance(
    parameters,
    drug,
    timesteps,
    artemisinin_resistance_proportion,
    partner_drug_resistance_proportion,
    slow_parasite_clearance_probability,
    early_treatment_failure_probability,
```

```

    late_clinical_failure_probability,
    late_parasitological_failure_probability,
    reinfection_during_prophylaxis_probability,
    slow_parasite_clearance_time
)

```

Arguments

parameters	the model parameters
drug	the index of the drug which resistance is being set, as set by the set_drugs() function, in the parameter list
timesteps	vector of time steps for each update to resistance proportion and resistance outcome probability
artemisinin_resistance_proportion	vector of updates to the proportions of infections that are artemisinin resistant at time t
partner_drug_resistance_proportion	vector of updates to the proportions of infections that are partner-drug resistant at time t
slow_parasite_clearance_probability	vector of updates to the proportion of artemisinin-resistant infections that result in early treatment failure
early_treatment_failure_probability	vector of updates to the proportion of artemisinin-resistant infections that result in slow parasite clearance
late_clinical_failure_probability	vector of updates to the proportion of partner-drug-resistant infections that result in late clinical failure
late_parasitological_failure_probability	vector of updates to the proportion of partner-drug-resistant infections that result in late parasitological failure
reinfection_during_prophylaxis_probability	vector of updates to the proportion of partner-drug-resistant infections that result in reinfection during prophylaxis
slow_parasite_clearance_time	single value representing the mean time individual's experiencing slow parasite clearance reside in the treated state

Description

The model will distribute bed nets at timesteps to a random sample of the entire human population. The sample size will be a proportion of the human population taken from the corresponding coverages. The sample *can* contain humans who already have bed nets.

All of the sample "use" their bed nets on the timestep after they are distributed. Incomplete usage is not part of this model.

If a human in the sample already has a bed net, their bed net will be replaced by a new one.

Using the gamman parameter:

Bed nets will be randomly removed each timestep with a rate of $1 - \exp(-1/\text{retention})$

Alternatively, the logistic retention parameters can be used. Retention time is calculated using the logistic decay function:

l (time at which all nets fail) = $\text{half_life} / \sqrt{1 - k / (k - \log(0.5))}$ T (simulated time for individual failure) = $l * \sqrt{a / (1 + a)}$, $a = -\log(U)/k$

The structure for the bed net model is documented in the S.I. of 10.1038/s41467-018-07357-w

Usage

```
set_bednets(
  parameters,
  timesteps,
  coverages,
  dn0,
  rn,
  rnm,
  gamman,
  retention = NULL,
  logistic_half_life = NULL,
  logistic_k = NULL
)
```

Arguments

parameters	a list of parameters to modify
timesteps	the timesteps at which to distribute bed nets
coverages	the proportion of the human population who receive bed nets
dn0	a matrix of death probabilities for each species over time. With nrow=length(timesteps), ncol=length(species)
rn	a matrix of repelling probabilities for each species over time With nrow=length(timesteps), ncol=length(species)
rnm	a matrix of minimum repelling probabilities for each species over time With nrow=length(timesteps), ncol=length(species)
gamman	a vector of bednet insecticide half-lives for each distribution timestep
retention	(optional) the average number of timesteps a net is kept for (modelled using a log uniform)

set_demography	<i>Parameterise variable deathrates</i>
----------------	---

Description

Parameterise variable deathrates

Usage

```
set_demography(parameters, agegroups, timesteps, deathrates)
```

Arguments

parameters	the model parameters
agegroups	vector of agegroups (in timesteps)
timesteps	vector of timesteps for each change in demography
deathrates	matrix of deathrates per age group per timestep. Rows are timesteps from the timesteps param. Columns are the age groups from the agegroups param.

set_drugs	<i>Parameterise drugs to use in the model</i>
-----------	---

Description

Parameterise drugs to use in the model

Usage

```
set_drugs(parameters, drugs)
```

Arguments

parameters	the model parameters
drugs	a list of drug parameters, can be set using presets

set_epi_outputs	<i>Parameterise age grouped output rendering</i>
-----------------	--

Description

Parameterise age grouped output rendering

Usage

```
set_epi_outputs(
  parameters,
  age_group = NULL,
  incidence = NULL,
  clinical_incidence = NULL,
  severe_incidence = NULL,
  prevalence = NULL,
  n_with_hypnozoites = NULL,
  ica = NULL,
  icm = NULL,
  iva = NULL,
  ivm = NULL,
  id = NULL,
  ib = NULL,
  iaa = NULL,
  iam = NULL,
  hypnozoites = NULL
)
```

Arguments

parameters	the model parameters
age_group	age breaks for population size outputs; default = NULL
incidence	age breaks for incidence outputs (D+Tr+A); default = NULL
clinical_incidence	age breaks for clinical incidence outputs (symptomatic); default = c(0, 1825)
severe_incidence	age breaks for severe incidence outputs (pf only); default = NULL
prevalence	age breaks for clinical prevalence outputs (pcr and lm detectable infections); default = c(730, 3650)
n_with_hypnozoites	age breaks for individuals with hypnozoites outputs (pv only); default = NULL
ica	age breaks for average acquired clinical immunity; default = NULL
icm	age breaks for average maternal clinical immunity; default = NULL
iva	age breaks for average acquired severe immunity (pf only); default = NULL

ivm	age breaks for average maternal severe immunity (pf only); default = NULL
id	age breaks for average immunity to detectability (pf only); default = NULL
ib	age breaks for average blood immunity (pf only); default = NULL
iaa	age breaks for average acquired antiparasite immunity (pv only); default = NULL
iam	age breaks for average maternal antiparasite immunity (pv only); default = NULL
hypnozoites	age breaks for average hypnozoite batches (pv only); default = NULL

Details

this function produces contiguous age groups, inclusive of the lower age limit and exclusive of the upper age limit: e.g., c(0, 10, 100) will produce two age groups: 0-9 and 10-99 in days.

set_equilibrium	<i>Set equilibrium</i>
-----------------	------------------------

Description

This will update the IBM parameters to match the equilibrium parameters and set up the initial human and mosquito population to achieve init_EIR

Usage

```
set_equilibrium(
  parameters,
  init_EIR,
  eq_params = NULL,
  EIR_population_input = "adult"
)
```

Arguments

parameters	model parameters to update
init_EIR	the desired initial EIR (infectious bites per adult person per year).
eq_params	parameters from the malariaEquilibrium package, if null The default malariaEquilibrium parameters will be used (not applicable for P. vivax).
EIR_population_input	the population corresponding with the initial EIR units, where options are "adult" (default) or "total".

set_mass_pev

Parameterise a vaccine mass distribution strategy

Description

distribute pre-erythrocytic vaccine to a population in an age range. Efficacy will take effect after the last dose

Usage

```
set_mass_pev(
  parameters,
  profile,
  timesteps,
  coverages,
  min_ages,
  max_ages,
  min_wait,
  booster_spacing,
  booster_coverage,
  booster_profile
)
```

Arguments

parameters	a list of parameters to modify
profile	a list of details for the vaccine profile, create with <code>create_pev_profile</code>
timesteps	a vector of timesteps for each round of vaccinations
coverages	the coverage for each round of vaccinations
min_ages	for the target population, inclusive (in timesteps)
max_ages	for the target population, inclusive (in timesteps)
min_wait	the minimum acceptable time since the last vaccination (in timesteps); When using both <code>set_mass_pev</code> and <code>set_pev_epi</code> , this represents the minimum time between an individual being vaccinated under one scheme and vaccinated under another.
booster_spacing	the timesteps (following the final primary dose) at which booster vaccinations are administered
booster_coverage	a matrix of coverages (timesteps x boosters) specifying the proportion the previously vaccinated population to continue receiving booster doses. The rows of the matrix must be the same size as <code>timesteps</code> . The columns of the matrix must be the same size as <code>booster_spacing</code> .
booster_profile	list of lists representing each booster profile, the outer list must be the same length as <code>booster_spacing</code> . Create vaccine profiles with <code>create_pev_profile</code>

set_mda

Parameterise a Mass Drug Administration

Description

Parameterise a Mass Drug Administration

Usage

```
set_mda(parameters, drug, timesteps, coverages, min_ages, max_ages)
```

Arguments

parameters	a list of parameters to modify
drug	the index of the drug to administer
timesteps	a vector of timesteps for each round of mda
coverages	a vector of the proportion of the target population who receive each round
min_ages	a vector of minimum ages of the target population for each round exclusive (in timesteps)
max_ages	a vector of maximum ages of the target population for each round exclusive (in timesteps)

set_parameter_draw

Use parameter draw from the join posterior

Description

Overrides default (median) model parameters with a single draw from the fitted joint posterior and appends parameter_draw to the parameters list. Must be called prior to set_equilibrium.

Usage

```
set_parameter_draw(parameters, draw)
```

Arguments

parameters	the model parameters
draw	the draw to use. Must be an integer between 1 and 1000

set_pev_epi

Parameterise a pre-erythrocytic vaccine with an EPI strategy

Description

distribute vaccine when an individual becomes a certain age. Efficacy will take effect after the last dose

Usage

```
set_pev_epi(
  parameters,
  profile,
  coverages,
  timesteps,
  age,
  min_wait,
  booster_spacing,
  booster_coverage,
  booster_profile,
  seasonal_boosters = FALSE
)
```

Arguments

parameters	a list of parameters to modify
profile	a list of details for the vaccine profile, create with <code>create_pev_profile</code>
coverages	a vector of coverages for the primary doses
timesteps	a vector of timesteps for each change in coverage
age	the age when an individual will receive the first dose of the vaccine (in timesteps)
min_wait	the minimum acceptable time since the last vaccination (in timesteps); When <code>seasonal_boosters = TRUE</code> , this represents the minimum time between an individual receiving the final dose and the first booster. When using both <code>set_mass_pev</code> and <code>set_pev_epi</code> , this represents the minimum time between an individual being vaccinated under one scheme and vaccinated under another.
booster_spacing	the timesteps (following the final primary dose) at which booster vaccinations are administered
booster_coverage	a matrix of coverages (timesteps x boosters) specifying the proportion the previously vaccinated population to continue receiving booster doses. The rows of the matrix must be the same size as <code>timesteps</code> . The columns of the matrix must be the same size as <code>booster_spacing</code> .
booster_profile	list of lists representing each booster profile, the outer list must be the same length as <code>booster_spacing</code> . Create vaccine profiles with <code>create_pev_profile</code>

seasonal_boosters

logical, if TRUE the first booster timestep is relative to the start of the year, otherwise they are relative to the last primary dose

set_pmc

Parameterise a perennial malaria chemoprevention (PMC, formerly IPI)

Description

Parameterise a perennial malaria chemoprevention (PMC, formerly IPI)

Usage

```
set_pmc(parameters, drug, timesteps, coverages, ages)
```

Arguments

parameters	a list of parameters to modify
drug	the index of the drug to administer
timesteps	a vector of timesteps for each change in coverage
coverages	a vector of proportions of the target population to receive the intervention
ages	a vector of ages at which PMC is administered (in timesteps)

set_smc

Parameterise a Seasonal Malaria Chemoprevention

Description

Parameterise a Seasonal Malaria Chemoprevention

Usage

```
set_smc(parameters, drug, timesteps, coverages, min_ages, max_ages)
```

Arguments

parameters	a list of parameters to modify
drug	the index of the drug to administer
timesteps	a vector of timesteps for each round of smc
coverages	a vector of the proportion of the target population who receive each round
min_ages	a vector of minimum ages of the target population for each round exclusive (in timesteps)
max_ages	a vector of maximum ages of the target population for each round exclusive (in timesteps) drug

set_species	<i>Parameterise the mosquito species to use in the model</i>
-------------	--

Description

Parameterise the mosquito species to use in the model

Usage

```
set_species(parameters, species, proportions)
```

Arguments

parameters	the model parameters
species	a list of species presets
proportions	a vector of proportions for each species

set_spraying	<i>Parameterise an indoor spraying strategy</i>
--------------	---

Description

The model will apply indoor spraying at timesteps to a random sample of the entire human population. The sample size will be a proportion of the human population taken from the corresponding coverages. The sample *can* contain humans who have already benefited from spraying.

If a human in the sample lives in a sprayed house, the efficacy of the spraying will be returned to the maximum.

The structure for the indoor residual spraying model is documented in the S.I. of 10.1038/s41467-018-07357-w

Usage

```
set_spraying(
  parameters,
  timesteps,
  coverages,
  ls_theta,
  ls_gamma,
  ks_theta,
  ks_gamma,
  ms_theta,
  ms_gamma
)
```

Arguments

parameters	a list of parameters to modify
timesteps	the timesteps at which to spray
coverages	the proportion of the population who get indoor spraying
ls_theta	matrix of mortality parameters With nrow=length(timesteps), ncol=length(species)
ls_gamma	matrix of mortality parameters per timestep With nrow=length(timesteps), ncol=length(species)
ks_theta	matrix of feeding success parameters per timestep With nrow=length(timesteps), ncol=length(species)
ks_gamma	matrix of feeding success parameters per timestep With nrow=length(timesteps), ncol=length(species)
ms_theta	matrix of deterrence parameters per timestep With nrow=length(timesteps), ncol=length(species)
ms_gamma	matrix of deterrence parameters per timestep With nrow=length(timesteps), ncol=length(species)

set_tbv

Parameterise an TBV strategy

Description

Parameterise an TBV strategy

Usage

```
set_tbv(parameters, timesteps, coverages, ages)
```

Arguments

parameters	a list of parameters to modify
timesteps	a vector of timesteps for each round of vaccinations
coverages	the coverage for each round of vaccinations
ages	a vector of ages of the target population (in years)

SP_AQ_params	<i>Preset parameters for the SP-AQ drug (P. falciparum)</i>
--------------	---

Description

Preset parameters for the SP-AQ drug (P. falciparum)

Usage

SP_AQ_params

Format

An object of class `numeric` of length 4.

Details

Use a vector of preset parameters for the SP-AQ drug (sulphadoxine-pyrimethamine and amodiaquine)

Default parameters, from L to R, are: `drug_efficacy`: 0.9, `drug_rel_c`: 0.32, `drug_prophylaxis_shape`: 4.3, `drug_prophylaxis_scale`: 38.1

steph_params	<i>Preset parameters for the An. stephensi vector</i>
--------------	---

Description

Preset parameters for the An. stephensi vector

Usage

steph_params

Format

An object of class `list` of length 7.

Details

Default parameters: `species`: "steph" `blood_meal_rates`: 0.3333333 `foraging_time`: .69 `Q0`: 0.21 `phi_bednets`: 0.57 `phi_indoors`: 0.37 `mum`: 0.112

parameters reference: [https://bmcmecine.biomedcentral.com/articles/10.1186/s12916-022-02324-](https://bmcmecine.biomedcentral.com/articles/10.1186/s12916-022-02324-1)

1 Values for `phi_bednets` and `phi_indoors` are from: https://github.com/arranhamlet/stephensi_ETH_publication/blob/297352
L21 values for `Q0`: are the average from: https://github.com/cwhittaker1000/stephenseasonality/blob/main/data/bionomic_sp

Index

* datasets

- AL_params, [3](#)
- arab_params, [3](#)
- CQ_params_vivax, [6](#)
- CQ_PQ_params_vivax, [7](#)
- CQ_TQ_params_vivax, [7](#)
- DHA_PQP_params, [9](#)
- fun_params, [10](#)
- gamb_params, [10](#)
- kol_params, [21](#)
- parameter_draws_pf, [21](#)
- parameter_draws_pv, [22](#)
- parasite_parameters, [23](#)
- r21_booster_profile, [24](#)
- r21_profile, [24](#)
- rtss_booster_profile, [25](#)
- rtss_profile, [25](#)
- SP_AQ_params, [43](#)
- steph_params, [43](#)

AL_params, [3](#)

arab_params, [3](#)

calculate_carrying_capacity, [4](#)

CorrelationParameters, [4](#)

CQ_params_vivax, [6](#)

CQ_PQ_params_vivax, [7](#)

CQ_TQ_params_vivax, [7](#)

create_pev_profile, [8](#)

create_progress_process, [8](#)

DHA_PQP_params, [9](#)

find_birthingrates, [9](#)

fun_params, [10](#)

gamb_params, [10](#)

get_antimalarial_resistance_parameters, [11](#)

get_correlation_parameters, [11](#)

get_init_carrying_capacity, [12](#)

get_parameters, [13](#)

kol_params, [21](#)

parameter_draws_pf, [21](#)

parameter_draws_pv, [22](#)

parameterise_mosquito_equilibrium, [22](#)

parameterise_total_M, [23](#)

parasite_parameters, [23](#)

peak_season_offset, [18, 24](#)

r21_booster_profile, [24](#)

r21_profile, [24](#)

rtss_booster_profile, [25](#)

rtss_profile, [25](#)

run_metapop_simulation, [26](#)

run_resumable_simulation, [27](#)

run_simulation, [27](#)

run_simulation_with_repetitions, [30](#)

set_antimalarial_resistance, [18, 30](#)

set_bednets, [18, 31](#)

set_carrying_capacity, [17, 33](#)

set_clinical_treatment, [17, 33](#)

set_demography, [34](#)

set_drugs, [17, 34](#)

set_epi_outputs, [35](#)

set_equilibrium, [36](#)

set_mass_pev, [18, 37](#)

set_mda, [18, 38](#)

set_parameter_draw, [16, 38](#)

set_pev_epi, [18, 39](#)

set_pmc, [18, 40](#)

set_smc, [18, 40](#)

set_species, [16, 41](#)

set_spraying, [18, 41](#)

set_tbv, [18, 42](#)

SP_AQ_params, [43](#)

steph_params, [43](#)