

Package: `odin.dust` (via `r-universe`)

October 2, 2024

Title Compile Odin to Dust

Version 0.3.13

Description Less painful than it sounds, this package compiles an odin model to use dust, our new stochastic model system. Supports only a subset of odin models (discrete time stochastic models with no interpolation and no delays).

License MIT + file LICENSE

Encoding UTF-8

Language en-GB

URL <https://github.com/mrc-ide/odin.dust>

BugReports <https://github.com/mrc-ide/odin.dust/issues>

Imports R6, brio, cpp11, decor, dust ($\geq 0.15.1$), odin ($\geq 1.5.0$),
tibble, vctrs

Suggests dde, knitr, mockery, pkgload, rmarkdown, socialmixr, testthat

RoxygenNote 7.2.2

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Remotes mrc-ide/dust, mrc-ide/odin

Repository <https://mrc-ide.r-universe.dev>

RemoteUrl <https://github.com/mrc-ide/odin.dust>

RemoteRef master

RemoteSha bb34b58b785b7a1724f76d236d847a31626288a5

Contents

<code>odin_dust</code>	2
<code>odin_dust_options</code>	3
<code>odin_dust_package</code>	4

Index	5
--------------	---

odin_dust	<i>Create a dust odin model</i>
-----------	---------------------------------

Description

Compile an odin model to work with dust.

Usage

```
odin_dust(x, ..., options = NULL)
```

```
odin_dust_(x, ..., options = NULL)
```

Arguments

x	Either the name of a file to read, a text string (if length is greater than 1 elements will be joined with newlines) or an expression.
...	Arguments passed to odin_dust_options , including <code>real_type</code> , <code>gpu</code> , <code>verbose</code> , <code>workdir</code> , <code>no_check_unused_equations</code> and <code>rewrite_dims</code> .
options	An odin::odin_options or odin_dust_options object. If given it overrides arguments; if it is already a <code>odin_dust_options</code> object it is returned unmodified. Otherwise it is passed through to odin::odin_options where it will override arguments in ... but respond to the <code>odin_dust</code> specific options (<code>real_type</code> , etc)

Details

Note that this does not (yet) support the full odin output object, instead creating the more limited dust interface. However, for many uses this should be considerably faster than the interface that odin normally uses (built on dde).

Including custom code

When including custom C++ code you may want to set additional options in order to enable compilation. You can do this by including pseudo-attributes

- `// [[odin.dust::cpp_std(C++17)]]` - use this to change the C++ standard used in compilation; this is passed to `dust::dust()` as the `cpp_std` option. It is only necessary to pass in values greater than C++11 at present as that is dust's default.
- `// [[odin.dust::linking_to(pkg)]]` - use this to make include files present in an R package (e.g., BH) available. You can use as many of these attributes as you need.

odin_dust_options	<i>Options for odin_dust</i>
-------------------	------------------------------

Description

Options for controlling [odin_dust](#); this is a superset of [odin::odin_options](#)

Usage

```
odin_dust_options(
    ...,
    real_type = NULL,
    rng_state_type = NULL,
    gpu = NULL,
    gpu_generate = NULL,
    compiler_options = NULL,
    optimisation_level = NULL,
    options = NULL
)
```

Arguments

...	Arguments passed to odin::odin_options , including verbose, workdir, no_check_unused_equations and rewrite_dims.
real_type	C++ type to use for real (floating point) numbers. Defaults to double.
rng_state_type	C++ type to use for the random number generator. Defaults to <code>dust::random::generator<real_type></code> which selects a generator based on your real type. The default prior to dust 0.10.0 was <code>dust::random::xoshiro256starstar_state</code> .
gpu	Experimental! Generate support for running models on a GPU. This implies <code>gpu_generate</code> but <i>does</i> require a gpu and nvcc toolchain. Currently not supported within package code. This argument will be passed through to dust::dust() and so to enable compilation for a gpu, pass either TRUE or the results of dust::dust_cuda_options
gpu_generate	Experimental Generate gpu support code. This does not require a gpu or nvcc toolchain, but creates code that could be compiled for a gpu. This is primarily intended for testing and development as the generated code will be slower than the normal cpu version, and the compilation time will be considerably slower. Currently not supported within package code.
compiler_options	Additional options for the C++ compiler, passed to dust::dust
optimisation_level	Shorthand control over optimisation level, passed to dust::dust . If provided should be one of none (slow running, fast building), standard or max (enables fast math)
options	An odin::odin_options or odin_dust_options object. If given it overrides arguments; if it is already a <code>odin_dust_options</code> object it is returned unmodified. Otherwise it is passed through to odin::odin_options where it will override arguments in ... but respond to the <code>odin_dust</code> specific options (<code>real_type</code> , etc)

Value

A list of options (class `odin_options`) to pass to `odin.dust::odin_dust`

Examples

```
odin.dust::odin_dust_options()
```

odin_dust_package	<i>Update package code</i>
-------------------	----------------------------

Description

Update generated code in a package that uses `odin` and `dust` to provide a model. This will generate new dust code in `inst/dust` and from that generate a full model in `src`, and an R interface in `R/dust.R`, along with the `cpp11` attributes that are needed to use the model.

Usage

```
odin_dust_package(path, options = NULL)
```

Arguments

path	Path to the package root (the directory that contains DESCRIPTION)
options	An odin::odin_options or odin_dust_options object. If given it overrides arguments; if it is already a <code>odin_dust_options</code> object it is returned unmodified. Otherwise it is passed through to odin::odin_options where it will override arguments in ... but respond to the <code>odin_dust</code> specific options (<code>real_type</code> , etc)

Value

The path to the package

Index

dust::dust, [3](#)
dust::dust(), [2](#), [3](#)
dust::dust_cuda_options, [3](#)

odin::odin_options, [2–4](#)
odin_dust, [2](#), [3](#)
odin_dust_(odin_dust), [2](#)
odin_dust_options, [2](#), [3](#), [3](#), [4](#)
odin_dust_package, [4](#)