

Package: odin.js (via r-universe)

June 23, 2024

Title 'odin' 'JavaScript' support

Version 0.1.11

Author Rich FitzJohn

Maintainer Rich FitzJohn <rich.fitzjohn@gmail.com>

Description Create 'JavaScript' differential equation models from an 'odin' model specification.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports R6 (>= 2.4.0), V8, jsonlite, odin (>= 1.2.2)

Suggests cinterpolate, deSolve, testthat

RoxygenNote 7.1.1

Remotes ropensci/jsonvalidate, mrc-ide/odin

Repository <https://mrc-ide.r-universe.dev>

RemoteUrl <https://github.com/mrc-ide/odin.js>

RemoteRef master

RemoteSha 23e6e3e9d7170cb42ea608a753be660c07b6bcd2

Contents

odin_js	2
odin_js_bundle	2
odin_js_example	3

Index	4
--------------	----------

odin_js	<i>Create a javascript odin model</i>
---------	---------------------------------------

Description

Generate a javascript odin model from a file, text string or expression.

Usage

```
odin_js(x, ..., options = NULL)
```

```
odin_js_(x, ..., options = NULL)
```

Arguments

x	Either the name of a file to read, a text string (if length is greater than 1 elements will be joined with newlines) or an expression.
...	Arguments passed to odin_options
options	An optional odin_options object. The target element (if present) will be overridden.

odin_js_bundle	<i>Create a bundle of odin models</i>
----------------	---------------------------------------

Description

Create a bundle of odin models

Usage

```
odin_js_bundle(  
  filenames,  
  dest = tempfile(),  
  include = NULL,  
  include_dopri = TRUE  
)
```

Arguments

filenames	Filenames with odin source code
dest	Destination file for the generated javascript
include	Optional vector of paths of filenames to include into the javascript bundle
include_dopri	Logical, indicating if the dopri solver should be included as well.

odin_js_example	<i>Generate a built in example</i>
-----------------	------------------------------------

Description

Generate a web page and javascript for a built-in example

Usage

```
odin_js_example(filename, name, dest = tempfile())
```

Arguments

filename	Filename of model to include
name	Name of the example (only simple is currently supported)
dest	Destination directory - multiple files will be created here, overwriting existing files without prompting.

Index

odin_js, [2](#)
odin_js_(odin_js), [2](#)
odin_js_bundle, [2](#)
odin_js_example, [3](#)
odin_options, [2](#)